



<http://icculus.org/manticore/>

© Benj Carson & Jeff Mrochuk

3D Performance (On the Apex20K200E)

Core Clock Frequency	50 MHz
Memory Clock Frequency	50 MHz
Memory	32 MB
Memory Bandwidth	(TBD)* MB/s
Max Fillrate	(TBD)* pixels/s
Max Triangle Rate	(TBD)* triangles/s

*To Be Determined

Note:

These speeds are based on FPGA technology. Speeds would be greatly increased with Custom IC technology, which is used by other 3D GPUs.

Video Timing

Horizontal Timing:		
Horizontal refresh	40.8 kHz	
Active	640 pixels	19.17µs
Front Porch	43 pixels	1.29 µs
Sync	46 pixels	1.38 µs
Back Porch	87 pixels	2.61 µs
Entire line	816 pixels	24.48 µs

Vertical Timing:		
Vertical refresh	76 Hz	
Active	480 lines	11.75 ms
Front Porch	9 lines	0.223 ms
Sync	3 lines	73.44 µs
Back Porch	30 lines	0.734 ms
Entire frame	522 lines	12.8 ms

Pinouts

SDRAM Module		
Pin Name	Direction	Number
Clock (CK)	output	2
Clock Enable (CKE)	output	2
Chip Select (S)	output	2
RAS, CAS, WE	output	3
Bank Address (BA)	output	2
Address (A)	output	13
Data (DQ)	input/output	64
Data I/O Mask (DQMB)	output	8
Serial Presence Detect (SDA)	input/output	1
Serial Presence Detect Clock (SCL)	output	1

Total: 98

VGA Module		
Pin Name	Direction	Number
Red	output	3
Green	output	3
Blue	output	2
Horizontal Sync	output	1
Vertical Sync	output	1

Total: 10

SDRAM Controller

Clock Speed	50MHz
Burst Length	4
CAS Latency	2
Timings	JEDEC Standard ¹

¹ JEDEC PC133 Design Spec 4-20-02R11b